


AD00003-7/3

AD00003-7/3

S11/S22/S21(SWR, SWR, dB)



BNC (P) SMA (P)  
ST L:33.2mm  
BO/NI,PI/GO,  
BNC/CAP/NI, SMA/CAP/GO

|                |               |
|----------------|---------------|
| Frequency      |               |
| Insertion Loss |               |
| VSWR           |               |
| Impedance      | ■ 50Ω □ 75Ω   |
| Temperature    | -40°C ~ 125°C |

|          |                    |
|----------|--------------------|
| ■_1.0GHz | - 1.11, 1.11, 0.02 |
| ■_2.0GHz | - 1.23, 1.23, 0.12 |
| ■_3.0GHz | - 1.19, 1.18, 0.11 |
| ■_4.0GHz | - 1.40, 1.38, 0.22 |
| ■_5.0GHz | - 1.52, 1.52, 0.31 |
| ■_6.0GHz | - 1.52, 1.44, 0.30 |
| ■_7.0GHz | - 1.65, 1.59, 0.46 |
| ■_8.0GHz | - 1.82, 1.79, 0.52 |

► NETWORK ANALYZER

► Test cable

► Test Adaptor

■ E5071B (~8.5GHz)

■ N Male to SMA Male

■ SMA (J) SMA (J) ST

□ ZVA50 (~50GHz)

10GHz Cable (CF00540-7/1)

AD00006-7/2

■ SMA (J) BNC (J) ST

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

