

AD00006-7/2

AD00006-7/2



SMA (J) SMA (J)
ST L:22.2mm
BO/GO, PI/GO

Frequency	
Insertion Loss	
VSWR	
Impedance	☒ 50Ω ☐ 75Ω
Temperature	-40℃ ~ 125℃

S11/S22/S21(SWR, SWR, dB)

■_1GHz	- 1.01, 1.01, 0.01
■_3GHz	- 1.01, 1.01, 0.03
■_6GHz	- 1.10, 1.10, 0.05
■_8GHz	- 1.17, 1.17, 0.07
■10GHz	- 1.13, 1.14, 0.06
■12GHz	- 1.03, 1.04, 0.04
■14GHz	- 1.15, 1.15, 0.07
■16GHz	- 1.18, 1.18, 0.08
■18GHz	- 1.07, 1.07, 0.08
■MaX_	- 1.19, 1.19, 0.09

► NETWORK ANALYZER ► Test cable ► Test Adaptor

- ☐ E5071B (~8.5GHz)
- ☒ ZVA50 (~50GHz)
- ☒ 2.4mm Male to 2.4mm Male
- 50GHz Cable

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

