

AD00013-7/1



BNC (J) SMA (P)

ST L:34.7mm

BO/NI,PI/GO,CAP/GO

AD00013-7/1

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40°C ~ 125°C

S11/S22/S21(SWR,SWR,dB)

■_1.0GHz - 1.11, 1.11, 0.03
■_2.0GHz - 1.12, 1.12, 0.11
■_3.0GHz - 1.07, 1.06, 0.14
■_4.0GHz - 1.05, 1.16, 0.34

■_5.0GHz - 1.28, 1.31, 0.31
■_6.0GHz - 1.31, 1.36, 0.36
■_7.0GHz - 1.34, 1.34, 0.26
■_8.0GHz - 1.45, 1.45, 0.33

► NETWORK ANALYZER

► Test cable

► Test Adaptor

■ E5071B (~8.5GHz)

■ N Male to SMA Male

■ SMA (J) SMA (J) ST

□ ZVA50 (~50GHz)

10GHz Cable (CF00540-7/1)

AD00006-7/2

■ SMA (J) BNC (P) ST

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

