


AD00028-7/1

AD00028-7/1



SMA (J) SMA (J) 4 HOLE/BH
12.7-8.64-2.6
L:22.2mm(7.8-1.5-12.9)
BO/GO, PI/GO

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40℃ ~ 125℃

S11/S22/S21(SWR, SWR, dB)

■_1GHz	- 1.01, 1.01, 0.01
■_3GHz	- 1.03, 1.02, 0.04
■_6GHz	- 1.01, 1.01, 0.06
■_8GHz	- 1.03, 1.03, 0.07
■10GHz	- 1.05, 1.04, 0.08
■12GHz	- 1.03, 1.01, 0.09
■14GHz	- 1.06, 1.06, 0.11
■16GHz	- 1.12, 1.10, 0.14
■18GHz	- 1.10, 1.09, 0.18
■MaX_	- 1.13, 1.10, 0.18

- ▶ NETWORK ANALYZER ▶ Test cable ▶ Test Adaptor
- E5071B (~8.5GHz) ■ 2.4mm Male to 2.4mm Male
■ ZVA50 (~50GHz) 50GHz Cable

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

