


AD00028-7/2



SMA (J) SMA (J) 4 HOLE/BH
□12.7-8.64-2.6
L:22.2mm(7.8-1.5-12.9)
BO/GO, PI/GO

AD00028-7/2

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40℃ ~ 125℃

S11/S22/S21(SWR, SWR, dB)

■_1GHz	-	1.00	1.00	0.01
■_3GHz	-	1.01	1.02	0.02
■_6GHz	-	1.04	1.05	0.04
■_8GHz	-	1.07	1.06	0.05
■10GHz	-	1.09	1.07	0.06
■12GHz	-	1.09	1.09	0.05
■14GHz	-	1.06	1.07	0.06
■16GHz	-	1.01	1.02	0.06
■18GHz	-	1.05	1.05	0.07
■MaX__-	-	1.09	1.09	0.30

► NETWORK ANALYZER

► Test cable

► Test Adaptor

□ E5071B (~8.5GHz)

■ 2.4mm Male to 2.4mm Male

■ ZVA50 (~50GHz)

50GHz Cable

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

Trc1 S11 SWR 100 mU/ Ref1 U Cal



Trc2 S22 SWR 100 mU/ Ref1 U Cal



Trc3 S21 dB Mag 1 dB / Ref0 dB Cal

