

AD00069-7/2

No.2-56/TAP



BNC (J) BNC (J) 4 HOLE
□ 17.5-12.7-No2-56/TAP
L:32.6mm(12.7-2.4-17.5)
BO/NI,PI/GO

AD00069-7/2

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40℃ ~ 125℃

S11/S22/S21(SWR, SWR, dB)

■ _1.0GHz	- 1.14, 1.13, 0.09
■ _2.0GHz	- 1.01, 1.01, 0.13
■ _3.0GHz	- 1.04, 1.05, 0.17
■ _4.0GHz	- 1.13, 1.16, 0.21

■ _5.0GHz	- 1.34, 1.39, 0.43
■ _6.0GHz	- 1.07, 1.09, 0.50
■ _7.0GHz	- 1.43, 1.53, 0.65
■ _8.0GHz	- 1.26, 1.26, 0.30

► NETWORK ANALYZER ► Test cable

► Test Adaptor

■ E5071B (~8.5GHz)

□ ZVA50 (~50GHz)

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

