


AD00086-7/3

AD00086-7/3

S11/S22/S21(SWR, SWR, dB)



OLD
design

NEW
design

N (J) TNC (P)
ST L:37.7mm
BO/NI, PI/GO, CAP/NI

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40℃ ~ 125℃

■_0.5GHz	- 1.03, 1.03, 0.00
■_1.0GHz	- 1.03, 1.03, 0.01
■_1.5GHz	- 1.03, 1.03, 0.03
■_2.0GHz	- 1.05, 1.05, 0.04
■_3.0GHz	- 1.11, 1.11, 0.07

■_4.0GHz	- 1.21, 1.19, 0.09
■_5.0GHz	- 1.25, 1.24, 0.09
■_6.0GHz	- 1.10, 1.11, 0.06

► NETWORK ANALYZER

► Test cable

► Test Adaptor

■ E5071B (~8.5GHz)

■ N Male to SMA Male

■ N (P) SMA (J) Agilent사

□ ZVA50 (~50GHz)

10GHz Cable (CF00540-7/1)

■ SMA (J) TNC (J) PE사

TR1 : IN PORT VSWR(S11), TR2 : OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

