

AD00139-7/2



N (J) N (P)
ST **PUSH-ON**

L:31.3mm

BO/NI,PI/GO,CAP/NI

PUSH-ON

AD00139-7/2

Frequency	
Insertion Loss	
VSWR	
Impedance	☒ 50Ω ☐ 75Ω
Temperature	-40°C ~ 125°C

S11/S22/S21(SWR,SWR,dB)

■_1.0GHz	- 1.06, 1.06, 0.00
■_2.0GHz	- 1.06, 1.06, 0.03
■_3.0GHz	- 1.01, 1.03, 0.03
■_4.0GHz	- 1.00, 1.01, 0.05
■_5.0GHz	- 1.10, 1.12, 0.07
■_6.0GHz	- 1.09, 1.13, 0.18
■_7.0GHz	- 1.02, 1.11, 0.30
■_8.0GHz	- 1.14, 1.08, 0.26

► NETWORK ANALYZER

► Test cable

► Test Adaptor

■ E5071B (~8.5GHz)

■ N Male to N Male

■ N (J) N (J) AD00379-7/2

□ ZVA50 (~50GHz)

10GHz Cable (CF00539-7/1)

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

