

AD00144-7/1

AD00144-7/1

Frequency	
Insertion Loss	
VSWR	
Impedance	☒ 50Ω ☐ 75Ω
Temperature	-40℃ ~ 125℃

S11/S22/S21(SWR, SWR, dB)

■	_1,0GHz	- 1,03,	1,03,	0,00
■	_2,0GHz	- 1,02,	1,02,	0,02
■	_3,0GHz	- 1,05,	1,05,	0,03
■	_4,0GHz	- 1,08,	1,08,	0,03
■	_5,0GHz	- 1,04,	1,02,	0,03
■	_6,0GHz	- 1,08,	1,05,	0,01
■	_7,0GHz	- 1,09,	1,07,	0,02
■	_8,0GHz	- 1,06,	1,05,	0,06



N(J) N(J) 4 HOLE
□25.4-18.2-3.2
L:55mm(27-3-25)
BO/SU, PI/GO

- ▶ NETWORK ANALYZER
- ▶ Test cable
- ▶ Test Adaptor
- E5071B (~8.5GHz)
- N Male to N Male
- ZVA50 (~50GHz)
- 10GHz Cable (CF00539-7/1)

TR1 : IN PORT VSWR(S11), TR2 : OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

