


AD00148-7/1



N (P) N (P)
RA L:38.6-38.6mm
BO/NI,PI/GO,CAP/NI

AD00148-7/1

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40℃ ~ 125℃

S11/S22/S21(SWR, SWR, dB)

■ _1.0GHz - 1.04, 1.05, 0.04
■ _2.0GHz - 1.07, 1.06, 0.10
■ _3.0GHz - 1.03, 1.07, 0.12
■ _4.0GHz - 1.07, 1.07, 0.17

■ _5.0GHz - 0.19, 1.28, 0.24
■ _6.0GHz - 1.07, 1.09, 0.38
■ _7.0GHz - 1.10, 1.25, 0.59
■ _8.0GHz - 1.17, 1.20, 0.38

► NETWORK ANALYZER

► Test cable

► Test Adaptor

■ E5071B (~8.5GHz)

■ N Male to N Male

■ N (J) N (J) AD00379-7/2

□ ZVA50 (~50GHz)

10GHz Cable (CF00539-7/1)

2EA

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

