

AD00162-7/3



SMA (J) SMA (J) 4 HOLE
□12.7-8.64-2.7
L:29.7mm(8-1.7-20)
BO/GO, PI/GO

AD00162-7/3

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40℃ ~ 125℃

S11/S22/S21(SWR, SWR, dB)

■_1GHz	- 1.03, 1.03, 0.02
■_3GHz	- 1.04, 1.04, 0.06
■_6GHz	- 1.02, 1.02, 0.07
■_8GHz	- 1.05, 1.05, 0.08
■10GHz	- 1.17, 1.17, 0.12
■12GHz	- 1.14, 1.15, 0.11
■14GHz	- 1.06, 1.06, 0.12
■16GHz	- 1.21, 1.20, 0.16
■18GHz	- 1.08, 1.07, 0.14
■MaX_	- 1.21, 1.20, 0.17

▶ NETWORK ANALYZER ▶ Test cable ▶ Test Adaptor

- ☐ E5071B (~8.5GHz)
- ☒ ZVA50 (~50GHz)
- ☒ 2.4mm Male to 2.4mm Male
- 50GHz Cable

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

