

AD00192-7/2

AD00192-7/2



N (P) SMA (J)
ST L:31.8mm
BO/NI, PI/GO, CAP/NI

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40°C ~ 125°C

S11/S22/S21(SWR, SWR, dB)

■_1.0GHz	- 1.06, 1.06, 0.01
■_2.0GHz	- 1.04, 1.04, 0.00
■_3.0GHz	- 1.08, 1.08, 0.02
■_4.0GHz	- 1.11, 1.11, 0.02
■_5.0GHz	- 1.06, 1.07, 0.03
■_6.0GHz	- 1.19, 1.17, 0.07

■_7.0GHz	- 1.20, 1.20, 0.07
■_8.0GHz	- 1.09, 1.09, 0.04

▶ NETWORK ANALYZER

▶ Test cable

▶ Test Adaptor

■ E5071B (~8.5GHz)

■ N Male to N Male

■ N (J) N (J) AD00379-7/2

□ ZVA50 (~50GHz)

10GHz Cable (CF00539-7/1)

TR1 : IN PORT VSWR(S11), TR2 : OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

