

AD00300-7/1

PIMD



7/16 DIN (J) 7/16 DIN (J)
ST L:46.5mm
BO/SU, PI/SI/5

AD00300-7/1

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40°C ~ 125°C

S11/S22/S21(SWR, SWR, dB)

■_1.0GHz - 1.00, 1.01, 0.01
■_2.0GHz - 1.10, 1.10, 0.05
■_3.0GHz - 1.06, 1.06, 0.04
■_4.0GHz - 1.05, 1.05, 0.04
■_5.0GHz - 1.04, 1.06, 0.04
■_6.0GHz - 1.21, 1.20, 0.11
■_7.0GHz - 1.19, 1.22, 0.12

■_8.0GHz - 1.12, 1.14, 0.05
MAX 7.4G - 9.42, 9.04, 12.1

► NETWORK ANALYZER

► Test cable

► Test Adaptor

■ E5071B (~8.5GHz)

■ N Male to N Male

■ 7/16 (P) N (J) AD00377-7/4

□ ZVA50 (~50GHz)

10GHz Cable (CF00539-7/1)

2EA

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

