

AD00311-7/1



26PKZ (J) SMA (J)  
ST L:32.2mm  
BO/GO, PI/GO

AD00311-7/1

|                |               |
|----------------|---------------|
| Frequency      |               |
| Insertion Loss |               |
| VSWR           |               |
| Impedance      | ■ 50Ω □ 75Ω   |
| Temperature    | -40°C ~ 125°C |

S11/S22/S21(SWR, SWR, dB)

|                             |
|-----------------------------|
| ■_1.0GHz - 1.00, 1.00, 0.32 |
| ■_2.0GHz - 1.07, 1.08, 0.37 |
| ■_3.0GHz - 1.15, 1.14, 0.37 |
| ■_4.0GHz - 1.18, 1.19, 0.37 |
| ■_5.0GHz - 1.05, 1.07, 0.33 |
| ■_6.0GHz - 1.09, 1.07, 0.24 |
| ■_7.0GHz - 1.08, 1.09, 0.17 |
| -----                       |
| ■_8.0GHz - 1.29, 1.30, 0.06 |

► NETWORK ANALYZER ► Test cable

► Test Adaptor

■ E5071B (~8.5GHz)

□ ZVA50 (~50GHz)

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

