


AD00369-7/1

SMA-MALE QUICK TEST



SMA (J) SMA (J) **PUSH ON**
ST L:22.2mm
BO/GO, PI/GO

AD00369-7/1

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40℃ ~ 125℃

S11/S22/S21(SWR, SWR, dB)

■_1GHz	- 1.00, 1.01, 0.01
■_3GHz	- 1.05, 1.06, 0.04
■_6GHz	- 1.12, 1.12, 0.06
■_8GHz	- 1.13, 1.14, 0.06
■_10GHz	- 1.11, 1.12, 0.06
■_12GHz	- 1.04, 1.04, 0.06
■_14GHz	- 1.14, 1.14, 0.08

■_16GHz	- 1.26, 1.26, 0.12
■_18GHz	- 1.27, 1.28, 0.13
■MaX_---	- 1.28, 1.27, 0.14

► NETWORK ANALYZER ► Test cable ► Test Adaptor

- E5071B (~8.5GHz) ■ 2.4mm Male to 2.4mm Male
■ ZVA50 (~50GHz) 50GHz Cable

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

