


AD00376-7/2

PIMD



7/16 DIN (J) N (J)
ST L:49mm
BO/SU/6, PI/SI/7

AD00376-7/2

Frequency	
Insertion Loss	
VSWR	
Impedance	☒ 50Ω ☐ 75Ω
Temperature	-40°C ~ 125°C

S11/S22/S21(SWR, SWR, dB)

■_1.0GHz	- 1.01, 1.01, 0.01
■_2.0GHz	- 1.05, 1.04, 0.03
■_3.0GHz	- 1.09, 1.10, 0.10
■_4.0GHz	- 1.02, 1.01, 0.08
■_5.0GHz	- 1.19, 1.18, 0.01

■_6.0GHz	- 1.01, 1.04, 0.01
■_7.0GHz	- 1.12, 1.13, 0.01
■_8.0GHz	- 1.14, 1.11, 0.31

► NETWORK ANALYZER

► Test cable

► Test Adaptor

■ E5071B (~8.5GHz)

■ N Male to N Male

■ 7/16 (P) N (J) AD00377-7/4

□ ZVA50 (~50GHz)

10GHz Cable (CF00539-7/1)

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

