


AD00377-7/2

PIMD



7/16 DIN (P) N (J)

ST L:49mm

BO/SU/6, PI/SI/7, CAP/NI

AD00377-7/2

Frequency	
Insertion Loss	
VSWR	
Impedance	☒ 50Ω ☐ 75Ω
Temperature	-40°C ~ 125°C

S11/S22/S21(SWR, SWR, dB)

■_1.0GHz	- 1.02, 1.02, 0.00
■_2.0GHz	- 1.03, 1.03, 0.03
■_3.0GHz	- 1.09, 1.08, 0.04
■_4.0GHz	- 1.05, 1.05, 0.08
■_5.0GHz	- 1.12, 1.12, 0.01
■_6.0GHz	- 1.04, 1.11, 0.02
■_7.0GHz	- 1.16, 1.07, 0.06
■_8.0GHz	- 1.08, 1.14, 0.11

► NETWORK ANALYZER

► Test cable

► Test Adaptor

■ E5071B (~8.5GHz)

■ N Male to N Male

■ 7/16 (J) N (J) AD00376-7/2

□ ZVA50 (~50GHz)

10GHz Cable (CF00539-7/1)

TR1 : IN PORT VSWR(S11), TR2 : OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

