



SMA (J) SMA (J) BH
Ø12.7 SUS
L:22.3mm(6-2.5-13.8)
BO/SUS, PI/GO

AD00387-7/1

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40℃ ~ 125℃

S11/S22/S21(SWR, SWR, dB)

■_1GHz	- 1.02, 1.02, 0.03
■_3GHz	- 1.03, 1.02, 0.06
■_6GHz	- 1.06, 1.06, 0.09
■_8GHz	- 1.12, 1.11, 0.11
■10GHz	- 1.13, 1.12, 0.12
■12GHz	- 1.16, 1.16, 0.13

■14GHz	- 1.27, 1.27, 0.17
■16GHz	- 1.29, 1.29, 0.18
■18GHz	- 1.14, 1.16, 0.14
■MaX_--	- 1.30, 1.30, 0.20

► NETWORK ANALYZER ► Test cable ► Test Adaptor

- ☐ E5071B (~8.5GHz)
- ☒ ZVA50 (~50GHz)
- ☒ 2.4mm Male to 2.4mm Male
- ☐ 50GHz Cable

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

