


AD00390-7/3

PIMD



7/16 DIN (J) 7/16 DIN (P)
ST L:43.5mm
BO/SU/3, PI/SI/7, CAP/SU

AD00390-7/3

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40℃ ~ 125℃

S11/S22/S21(SWR, SWR, dB)

■_1.0GHz	- 1.02, 1.02, 0.00
■_2.0GHz	- 1.07, 1.06, 0.04
■_3.0GHz	- 1.01, 1.02, 0.05
■_4.0GHz	- 1.02, 1.03, 0.07
■_5.0GHz	- 1.12, 1.12, 0.07
■_6.0GHz	- 1.13, 1.14, 0.07
■_7.0GHz	- 1.13, 1.19, 0.15
■_8.0GHz	- 1.03, 1.04, 0.03
MAX 4.6G	- 4.58, 5.21, 9.17

► NETWORK ANALYZER

► Test cable

► Test Adaptor

■ E5071B (~8.5GHz)

■ N Male to N Male

■ 7/16 (P) N (J) AD00377-7/4

□ ZVA50 (~50GHz)

10GHz Cable (CF00539-7/1)

■ 7/16 (J) N (J) AD00376-7/2

TR1 : IN PORT VSWR(S11), TR2 : OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

