


AD00405-7/1

D/CUT-10.3



SMA (J) TNC (J) BH
L:33mm(9.1-3.1-20.8)
BO/NI, PI/GO

AD00405-7/1

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40°C ~ 125°C

S11/S22/S21(SWR, SWR, dB)

■ _1.0GHz - 1.05, 1.05, 0.04
■ _2.0GHz - 1.12, 1.12, 0.04
■ _3.0GHz - 1.03, 1.04, 0.04
■ _4.0GHz - 1.16, 1.17, 0.00
■ _5.0GHz - 1.14, 1.17, 0.04

■ _6.0GHz - 1.24, 1.25, 0.10
■ _7.0GHz - 1.30, 1.33, 0.13
■ _8.0GHz - 1.28, 1.31, 0.15

► NETWORK ANALYZER ► Test cable

► Test Adaptor

■ E5071B (~8.5GHz)

□ ZVA50 (~50GHz)

1 Active Ch/Trace 2 Response 3 Stimulus 4 Mkr/Analysis 5 Instr State



Tr3 S21 Log Mag 1.000dB/ Ref 0.000dB [F2]



1 Start 30 MHz IFBW 70 kHz Stop 8.5 GHz Cor

Meas Stop ExtRef Ready Svc 2020-02-24 15:06

System

Print

Abort Printing

Printer Setup...

Invert Image
ON

Dump
Screen Image...

Multipoint Test Set
Setup

Misc Setup

Backlight
ON

Firmware
Revision

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)