

AD00406-7/1

D/CUT-8.7



BNC (J) SMA (J) BH
L:33.5mm(10.8-2.3-20.4)
BO/NI, PI/GO

AD00406-7/1

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40°C ~ 125°C

S11/S22/S21(SWR, SWR, dB)

■ _1.0GHz	- 1.12, 1.12, 0.01
■ _2.0GHz	- 1.07, 1.07, 0.04
■ _3.0GHz	- 1.09, 1.09, 0.06
■ _4.0GHz	- 1.26, 1.26, 0.14
■ _5.0GHz	- 1.31, 1.25, 0.20
■ _6.0GHz	- 1.21, 1.08, 0.31
■ _7.0GHz	- 1.20, 1.18, 0.15
■ _8.0GHz	- 1.49, 1.45, 0.26

► NETWORK ANALYZER

► Test cable

► Test Adaptor

■ E5071B (~8.5GHz)

■ N Male to SMA Male

■ BNC (P) SMA (J) ST

□ ZVA50 (~50GHz)

10GHz Cable (CF00540-7/1)

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

