


AD00435-7/1

COVER/GASKET



N (J) N (P)

RA L:34.6-33.8mm

BO/NI, PI/GO, CAP/NI

AD00435-7/1

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40°C ~ 125°C

S11/S22/S21(SWR, SWR, dB)

■_1.0GHz - 1.05, 1.05, 0.02
■_2.0GHz - 1.07, 1.07, 0.05
■_3.0GHz - 1.13, 1.14, 0.07
■_4.0GHz - 1.11, 1.11, 0.09

■_5.0GHz - 1.22, 1.24, 0.12
■_6.0GHz - 1.11, 1.14, 0.15
■_7.0GHz - 1.29, 1.05, 0.60
■_8.0GHz - 1.25, 1.25, 0.14

▶ NETWORK ANALYZER

▶ Test cable

▶ Test Adaptor

■ E5071B (~8.5GHz)

■ N Male to N Male

■ N (J) N (J) AD00379-7/2

□ ZVA50 (~50GHz)

10GHz Cable (CF00539-7/1)

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

