

AD00451-7/1



PUSH ON



SMA (J) SMA (P)

PUSH ON JACK/CNC★

RA L:16.7-15.7mm

BO/GO, PI/GO, CAP/GO

AD00451-7/1	
Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40℃ ~ 125℃

S11/S22/S21(SWR,SWR,dB)	
■_1GHz	- 1.01, 1.02, 0.06
■_3GHz	- 1.01, 1.01, 0.13
■_6GHz	- 1.06, 1.12, 0.23

■_8GHz	- 1.24, 1.27, 0.38
■10GHz	- 1.45, 1.36, 0.81
■12GHz	- 1.73, 1.49, 0.76
■14GHz	- 1.81, 1.65, 0.87
■16GHz	- 1.78, 1.80, 0.79
■18GHz	- 2.29, 2.23, 1.11
■MaX_--	- 2.29, 2.29, 1.11

- ▶ NETWORK ANALYZER
- ▶ Test cable
- ▶ Test Adaptor
- E5071B (~8.5GHz)

■ ZVA50 (~50GHz)
- 2.4mm Male to 2.4mm Male

50GHz Cable
- AD00644-7/2

2.92mm (J) to 2.92mm(J)

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

