


AD00467-7/2



7/16 DIN (J) N (J) 4 HOLE

□40-29.8-4.5

L:37mm(15-4-18)

BODY/Nickel PIN/Silver

## AD00467-7/2

|                |             |
|----------------|-------------|
| Frequency      |             |
| Insertion Loss |             |
| VSWR           |             |
| Impedance      | ■ 50Ω □ 75Ω |
| Temperature    | -40℃ ~ 125℃ |

## S11/S22/S21(SWR, SWR, dB)

|          |                    |
|----------|--------------------|
| ■_1.0GHz | - 1.04, 1.04, 0.01 |
| ■_2.0GHz | - 1.02, 1.02, 0.02 |
| ■_3.0GHz | - 1.02, 1.04, 0.01 |
| ■_4.0GHz | - 1.19, 1.19, 0.53 |
| ■_5.0GHz | - 1.14, 1.13, 0.02 |
| ■_6.0GHz | - 1.03, 1.13, 0.04 |
| -----    |                    |
| ■_7.0GHz | - 1.29, 1.02, 0.01 |
| ■_8.0GHz | - 1.38, 1.28, 0.03 |

### ► NETWORK ANALYZER

■ E5071B (~8.5GHz)

□ ZVA50 (~50GHz)

### ► Test cable

■ N Male to N Male

10GHz Cable (CF00539-7/1)

### ► Test Adaptor

■ 7/16 (P) N (J) AD00377-7/4

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

