


AD00545-7/1

PIMD



4.1/9.5 DIN (P) N (J)  
ST L:36mm

BO/SU/5, PI/SI/5, CAP/NI

AD00545-7/1

|                |               |
|----------------|---------------|
| Frequency      |               |
| Insertion Loss |               |
| VSWR           |               |
| Impedance      | ■ 50Ω □ 75Ω   |
| Temperature    | -40°C ~ 125°C |

S11/S22/S21(SWR, SWR, dB)

|           |                    |
|-----------|--------------------|
| ■ _1.0GHz | - 1.01, 1.01, 0.38 |
| ■ _2.0GHz | - 1.04, 1.04, 0.34 |
| ■ _3.0GHz | - 1.16, 1.14, 0.33 |
| -----     |                    |
| ■ _4.0GHz | - 1.24, 1.23, 0.31 |
| ■ _5.0GHz | - 1.23, 1.22, 0.25 |
| ■ _6.0GHz | - 1.24, 1.24, 0.20 |
| ■ _7.0GHz | - 1.19, 1.21, 0.18 |
| ■ _8.0GHz | - 1.36, 1.37, 0.29 |

► NETWORK ANALYZER

► Test cable

► Test Adaptor

■ E5071B (~8.5GHz)

□ ZVA50 (~50GHz)

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

