


AD00553-7/1

PIMD



4.1/9.5 DIN (J)

7/16 DIN (P)

ST L:43mm

BO/SU/5, PI/SI/5, CAP/SU

AD00553-7/1

|                |               |
|----------------|---------------|
| Frequency      |               |
| Insertion Loss |               |
| VSWR           |               |
| Impedance      | ■ 50Ω □ 75Ω   |
| Temperature    | -40°C ~ 125°C |

S11/S22/S21(SWR, SWR, dB)

|          |                    |
|----------|--------------------|
| ■_1.0GHz | - 1.01, 1.01, 0.39 |
| ■_2.0GHz | - 1.01, 1.03, 0.36 |
| ■_3.0GHz | - 1.10, 1.08, 0.60 |
| ■_4.0GHz | - 1.14, 1.13, 0.25 |
| ■_5.0GHz | - 1.17, 1.17, 0.19 |
| ■_6.0GHz | - 1.04, 1.02, 0.10 |
| ■_7.0GHz | - 1.07, 1.04, 0.07 |
| ■_8.0GHz | - 1.17, 1.16, 0.15 |

► NETWORK ANALYZER

► Test cable

► Test Adaptor

■ E5071B (~8.5GHz)

□ ZVA50 (~50GHz)

TR1 : IN PORT VSWR(S11), TR2 : OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

