

AD00589-7/3

AD00589-7/3

S11/S22/S21(SWR, SWR, dB)



7/16 DIN (J) TNC (J)
4 HOLE □32-24.8-4.2
L:57.4mm(35-5-17.4)
BO/NI/TIN, PI/SI

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40℃ ~ 125℃

■ _1.0GHz - 1.04, 1.04, 0.05
■ _2.0GHz - 1.10, 1.09, 0.10
■ _3.0GHz - 1.11, 1.13, 0.11
■ _4.0GHz - 1.17, 1.18, 0.15

■ _5.0GHz - 1.01, 1.01, 0.11
■ _6.0GHz - 1.21, 1.22, 0.20
■ _7.0GHz - 1.29, 1.36, 0.24
■ _8.0GHz - 1.15, 1.22, 0.28

▶ NETWORK ANALYZER

▶ Test cable

▶ Test Adaptor

■ E5071B (~8.5GHz)

■ N Male to N Male

■ 7/16 (P) N (J) AD00377-7/4

□ ZVA50 (~50GHz)

10GHz Cable (CF00539-7/1)

■ SMA (J) TNC (P) PE사

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

