


AD00603-7/1

PIMD



4.3/10 DIN (P)

7/16 DIN (J)

ST L:46.8mm

BO/SU, PI/SI/3, CAP/NI

AD00603-7/1

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40°C ~ 125°C

S11/S22/S21(SWR, SWR, dB)

■ _1.0GHz - 1.02, 1.02, 0.04
■ _2.0GHz - 1.11, 1.11, 0.06
■ _3.0GHz - 1.11, 1.11, 0.11
■ _4.0GHz - 1.07, 1.09, 0.12

■ _5.0GHz - 1.28, 1.27, 0.19
■ _6.0GHz - 1.25, 1.28, 0.21
■ _7.0GHz - 1.37, 1.39, 0.30
■ _8.0GHz - 1.49, 1.36, 1.86
MaX 6.6G - 1.57, 1.57, 2.09

▶ NETWORK ANALYZER

▶ Test cable

▶ Test Adaptor

■ E5071B (~8.5GHz)

■ N Male to N Male

■ 4.3/10 (J) N (J) AD00582-7/1

□ ZVA50 (~50GHz)

10GHz Cable (CF00539-7/1)

■ 7/16 (P) N (J) AD00377-7/4

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

