


AD00609-7/1

PIMD

이원합금



7/16 DIN (P)

TNC (J)

ST L:51.5mm

BO/NI/TIN, PI/SI, CAP/SU

AD00609-7/1

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40℃ ~ 125℃

S11/S22/S21(SWR, SWR, dB)

■ _1.0GHz - 1.07, 1.06, Q05
■ _2.0GHz - 1.13, 1.13, Q11
■ _3.0GHz - 1.07, 1.12, Q21
■ _4.0GHz - 1.19, 1.18, Q22

■ _5.0GHz - 1.18, 1.18, Q17
■ _6.0GHz - 1.28, 1.31, Q24
■ _7.0GHz - 1.15, 1.22, Q25
■ _8.0GHz - 1.17, 1.26, Q37

▶ NETWORK ANALYZER

▶ Test cable

▶ Test Adaptor

■ E5071B (~8.5GHz)

■ N Male to N Male

■ 7/16 (J) N (J) AD00376-7/2

□ ZVA50 (~50GHz)

10GHz Cable (CF00539-7/1)

■ SMA (J) TNC (P) PE사

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

