


AD00633-7/1

IPX4



SMBL (J)

SMBL (J)

ST L:18mm

BO/NI, PI/GO

AD00633-7/1

Frequency	
Insertion Loss	
VSWR	
Impedance	☒ 50Ω ☐ 75Ω
Temperature	-40℃ ~ 125℃

S11/S22/S21 (SWR, SWR, dB)			
■_1.0GHz	-	1.02, 1.02, 0.05	
■_2.0GHz	-	1.00, 1.00, 0.11	
■_3.0GHz	-		
■_4.0GHz	-	1.00, 1.00, 0.18	
■_5.0GHz	-	1.09, 1.08, 0.20	

■_6.0GHz	-	1.26, 1.26, 0.29	
■_7.0GHz	-	1.39, 1.38, 0.34	
■_8.0GHz	-	1.32, 1.32, 0.30	

▶ NETWORK ANALYZER

▶ Test cable

▶ Test Adaptor

- ☐ E5071B (~8.5GHz)

☒ N Male to SMA Male
- ☐ ZVA50 (~50GHz)

10GHz Cable (CF00540-7/1)
- ☒ ZND (~8.5GHz)

TR1 : IN PORT VSWR(S11), TR2 : OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

