


AD00637-7/1

PIMD



4.3/10 DIN (P)

7/16 DIN (P)

ST L:41.6mm

BO/SU, PI/SI/3, CAP/NI

AD00637-7/1

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40°C ~ 125°C

S11/S22/S21 (dB)

■ _1.0GHz	- 1.01, 1.01, 0.04
■ _2.0GHz	- 1.10, 1.09, 0.02
■ _3.0GHz	- 1.07, 1.07, 0.00
■ _4.0GHz	- 1.12, 1.13, 0.03
■ _5.0GHz	- 1.07, 1.06, 0.06

■ _6.0GHz	- 1.22, 1.20, 0.12
■ _7.0GHz	- 1.23, 1.15, 0.31
■ _8.0GHz	- 1.42, 1.05, 1.10
MAX 7.9G	- 1.46, 1.25, 1.11

► NETWORK ANALYZER

► Test cable

► Test Adaptor

■ E5071B (~8.5GHz)

■ N Male to N Male

■ 4.3/10 (J) N (J) AD00582-7/1

□ ZVA50 (~50GHz)

10GHz Cable (CF00539-7/1)

■ 7/16 (J) N (J) AD00376-7/2

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

