


AD00638-7/1

PIMD



4.3/10 DIN (P)
N (P)
ST L:40mm
BO/SU, PI/SI/3, CAP/NI

AD00638-7/1

Frequency	
Insertion Loss	
VSWR	
Impedance	☒ 50Ω ☐ 75Ω
Temperature	-40℃ ~ 125℃

S11/S22/S21(SWR, SWR, dB)

■_1.0GHz	- 1.05, 1.05, 0.03
■_2.0GHz	- 1.04, 1.04, 0.02
■_3.0GHz	- 1.14, 1.14, 0.04
■_4.0GHz	- 1.19, 1.21, 0.07
■_5.0GHz	- 1.05, 1.05, 0.10
■_6.0GHz	- 1.18, 1.22, 0.13
■_7.0GHz	- 1.14, 1.12, 0.18

■_8.0GHz	- 1.50, 1.29, 0.96
MAX 8.1G	- 2.27, 1.89, 3.53

- ▶ NETWORK ANALYZER
- ▶ Test cable
- ▶ Test Adaptor
- ☒ E5071B (~8.5GHz)

☒ N Male to N Male

☒ 4.3/10 (J) N (J) AD00582-7/1
- ☐ ZVA50 (~50GHz)

10GHz Cable (CF00539-7/1)

☒ N (J) N (J) AD00379-7/2

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

