


AD00639-7/1

PIMD



4.3/10 DIN (J)

N (P)

S T L:39mm

BO/SU, PI/SI/3, CAP/NI

AD00639-7/1

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40°C ~ 125°C

S11/S22/S21(SWR,SWR,dB)

■ _1.0GHz - 1.02, 1.03, 0.05
■ _2.0GHz - 1.08, 1.08, 0.00
■ _3.0GHz - 1.10, 1.10, 0.01
■ _4.0GHz - 1.12, 1.13, 0.03
■ _5.0GHz - 1.14, 1.16, 0.10
■ _6.0GHz - 1.04, 1.04, 0.10
■ _7.0GHz - 1.01, 1.01, 0.10
■ _8.0GHz - 1.07, 1.08, 0.10
MaX 4.6G - 1.17, 1.17, 0.16

► NETWORK ANALYZER

► Test cable

► Test Adaptor

■ E5071B (~8.5GHz)

■ N Male to N Male

■ 4.3/10 (P) N (J) 구매품 1EA

□ ZVA50 (~50GHz)

10GHz Cable (CF00539-7/1)

■ N (J) N (J) AD00379-7/2 1EA

TR1 : IN PORT VSWR(S11), TR2 : OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

