


AD00642-7/4

SUS



2.4mm (J)
2.4mm (P)
ST L:18.1mm

BO/SUS, PI/GO/1.3, CAP/SUS

AD00642-7/4	
Frequency	~50GHz
Insertion Loss	
VSWR	1.20
Impedance	☒ 50Ω ☐ 75Ω
Temperature	-40℃ ~ 125℃

S11/S22/S21(SWR, SWR, dB)	
☒ _1GHz -	
☒ _6GHz -	
☒ _12GHz -	
☒ _18GHz -	
☒ _24GHz -	
☒ _30GHz -	
☒ _36GHz -	
☒ _42GHz -	
☒ _50GHz -	
☒ MaX - 1.07, 1.13, 0.25	

- ▶ NETWORK ANALYZER

☐ E5071B (~8.5GHz)

☒ ZVA50 (~50GHz)
- ▶ Test cable

☒ 2.4mm Male to 2.4mm Male 50GHz Cable
- ▶ Test Adaptor

☒ 2.4mm (J) to 2.92mm (J) AD00666-7/1

☒ 2.4mm (P) to 2.92mm (J) AD00643-7/2

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

