

Mate compatible table	
SMA [~18GHz]	Mate
3.5mm [~26.5GHz]	
2.92mm(K) [~40GHz]	
2.4mm [~50GHz]	Mate
1.85mm(V) [~65GHz]	

Un mate

2.4mm Female

4- ϕ 2.6 Thru

2-M7x0.75-6g

IDENTIFICATION
GROOVE (2.4mm)

2.4mm Female

2.4mm

8.6

SQ12.7

ϕ 15.8

8.6

ELECTRICAL DATA

1. IMPEDANCE : 50ohm
2. FREQUENCY RANGE : DC~50GHz
3. VSWR (Max) : 1.25

REVISION				
REV	DESCRIPTION	DRAWN	APPR	DATE
IR	Initial Registration	I.C.KIM		2020.12.29.

4	INSERT	1	SUS303		DIS00283-5/Q
3	INSULATOR	1	ULTEM1000		DIN03181-N/1
2	CONTACT	1	BeCu C17300	Gold Plate 1.3 μ m	DAC03351-5/F
1	BODY	1	SUS303	Passivate	DAD00404-5/4
NO.	DESCRIPTION	Q'TY	MATERIAL	PLATING	CODE

TOLERANCE	Decimal	DATE 2020. 12. 29.			 RF & MICROWAVE TECHNOLOGY Tel : 82-32-347-8015 Fax : 82-32-347-8017			
	Angle	APPROVED BY						
MATERIAL	$\pm 1^{\circ}$	CHECKED BY			TITLE 2.4mm (J) 2.4mm (J) 4H ADAPTOR			
	_____	DRAWN BY I.C.KIM						
FINISH	_____	SCALE	UNIT		A4	DWG NO.	AD00672-7/7	
		4/1	mm			REVISION	I R	SHEET 1 of 1