

REVISION				
REV	DESCRIPTION	DRAWN	APPR	DATE
IR	Initial Registration	S.Y.EUN	S.H.KIM	2022.12.01.
1	[실변치리No. 202301-0001] 고객사 요청 플랜지 가스켓 안착 내경 사이즈 변경 요청	S.H.KIM		2023.01.04.
2	DUST CAP 회전토크 개선 코드 변경	S.H.KIM		2023.10.30.

A

B

C

D

SMA DUST CAP

1/4-36 UNS-2A

7.8

15.0

24.5

4- ϕ 2.6 ϕ 20.0 ϕ 7.0 ϕ 8.9 ϕ 7.5

11.2


11.2

15.0

* 전기적 특성

1	Frequency range	DC ~ 4GHz
2	Impedance	50ohm NOMINAL
3	V.S.W.R	1.2 : 1 (Max)
4	Insertion loss	-0.3dB (Min)

2	7	DUST CAP	1	MBsBD C3604BD-F	이원합금 (Ni/Tin)	CN03144-N/6 CN03144-N/5
	6	JACK	1	MBsBD C3604BD-F	Nickel Plate	DJA00159-5/5
1	5	GASKET	1	SILICONE		DGK00028-N/1 DGK00024-N/1
	4	INSULATOR	1	TEFLON		DIN02179-N/1
1	3	INSULATOR	1	TEFLON		DIN00112-N/1
	2	CONTACT	1	BeCu C17300	Gold Plate	DAC03410-5/1
	1	BODY	1	MBsBD C3604BD-F	이원합금 (Ni/Tin)	DAD00460-5/2 DAD00460-5/1
	NO.	DESCRIPTION	Q'TY	MATERIAL	PLATING	CODE

TOLERANCE	Decimal ±0.1	DATE 2023. 10. 30.			 RF & MICROWAVE TECHNOLOGY Tel : 82-32-347-8015 Fax : 82-32-347-8017
	Angle ±1°	APPROVED BY			
MATERIAL _____		CHECKED BY			TITLE SMA50 (J) SMBL50 (J) 4HOLE ADAPTOR
FINISH _____		DRAWN BY S.H.KIM			
		SCALE 3/1	UNIT mm		DWG NO. AD00747-7/2
					REVISION 2
					SHEET 1 of 1

A

B

C

D