

REVISION				
REV	DESCRIPTION	DRAWN	APPR	DATE
1	Initial Registration	S.Y.EUN	S.H.KIM	2022.07.06.



* ELECTRICAL SPECIFICATIONS
Frequency Range : 5.8GHz~5.92GHz
Insertion Loss (Min.) : -0.4dB
V.S.W.R (Max.) : 1.25
Impedance : 50Ω
방수 : IP67
Impulse Discharge Voltage : 6kV(1.2/50μs) / 3kA (8/20μs)

13	END CAP (Female)	1	PVC	RED	DGK00141-N/1
12	EPOXY (경화제519)	1	—	—	CAD00021-N/2 (경화제_519)
11	EPOXY (주제519)	1	—	—	CAD00021-N/1(주제_519)
10	LABEL	1	은무데드종	—	DLA00870-8/1
9	GAS TUBE	1	—	—	DGT00010-N/1
8	COVER	1	MBsBD C3604BD-F	Nickel Plate	DCS00063-5/1
7	INSULATOR	2	TEFLON		DIN03160-N/1
6	GASKET	1	SILICONE RUB	RED	DGK00013-N/1
5	GASKET	1	SILICONE RUB	RED	DGK00036-N/1
4	CONTACT (B)	1	BeCu C17300	Gold Plate	DCT00693-5/2
3	CONTACT (A)	1	MBsBD C3604BD-F	Gold Plate	DCT04141-5/2
2	BODY(B)	1	MBsBD C3604BD-F	Nickel Plate	DBD04842-5/1
1	BODY(A)	1	MBsBD C3604BD-F	Nickel Plate	DBD04841-5/1
NO.	DESCRIPTION	Q'TY	MATERIAL	PLATING	CODE

TOLERANCE	Decimal ±0.3	DATE	2022. 07. 06.		 COMTECH RF & MICROWAVE TECHNOLOGY Tel : 82-32-347-8015 Fax : 82-32-347-8017		
	Angle ±1°	APPROVED BY	S.H.KIM				
MATERIAL		CHECKED BY			TITLE NP SMAJ(1/4λ) ARRESTOR 5800~5920 MHz		
		DRAWN BY	S.Y.EUN				
FINISH		SCALE	UNIT	 A3	DWG NO.	AS00152-7/1	
		2.5/1	mm		REVISION	I R	SHEET