

REVISION				
REV	DESCRIPTION	DRAWN	APPR	DATE
IR	Initial Registration	E.H.KIM	I.C.KIM	2013.07.22.
1	특성 Data 관리 구성 양식 변경	I.C.KIM		2016.12.08.

ELECTRICAL SPECIFICATIONS				
Frequency Range : DC~3GHz				
KJ CODE	Attenuation Value & Accuracy (dB)	V.S.W.R (Max)	Impedance (Nominal)	Power
AT00086-7A	30 ± 1.0	1.2	50ohm	2 Watt

15	LABEL	1			DLA00504-8/1
14	ATTENUATOR	1			DRE00473-N/1
13	PCB	1	FR4		DPC00416-9/2
12	SPRING WASHER	2	BeCu	Nickel Plate	DWA00069-5/1
11	FLAT WASHER	1	BsS	Nickel Plate	DWA00015-5/1
10	FLAT WASHER	2	BsS	Nickel Plate	DWA00016-5/1
9	CAP	1	MBsBD C3604BD-F	Nickel Plate	DCU00044-5/1
8	INSULATOR	1	TEFLON		DIN02211-N/1
7	INSULATOR	1	TEFLON		DIN02210-N/1
6	GASKET	1	SILICONE RUB	RED	DGK00186-N/1
5	GASKET	1	SILICONE RUB	RED	DGK00012-N/1
4	CONTACT	1	MBsBD C3604BD-F	Gold Plate	DCT02881-5/1
3	CONTACT	1	BeCu C17300	Gold Plate	DCT02880-5/1
2	BODY	1	MBsBD C3604BD-F	Nickel Plate	DBD03390-5/1
1	BODY	1	MBsBD C3604BD-F	Nickel Plate	DBD03389-5/1
NO.	DESCRIPTION	Q'TY	MATERIAL	PLATING	CODE

TOLERANCE	Decimal	DATE 2016. 12. 08.			 RF & MICROWAVE TECHNOLOGY Tel : 82-32-347-8015 Fax : 82-32-347-8017	
	Angle	APPROVED BY				
	±0.1					
MATERIAL	±1°	CHECKED BY				TITLE BNC50(J) - BNC50(P) ATTENUATOR _ 30dB
	-	DRAWN BY I.C.KIM				
FINISH	-	SCALE 3/1	UNIT mm			A4
					REVISION 1	SHEET 1 of 1

