

REVISION				
REV	DESCRIPTION	DRAWN	APPR	DATE
1	Initial Registration	T.J.KIM	J.H.YOUN	2015.07.09
2	4.1/9.5 Mini Din -> 4.3/10 Mini Din으로 변경	T.J.KIM	J.H.YOUN	2016.03.25

FEMALE GUIDE(5223957-A1)

깊이 외관표면으로부터 23.4mm

내부 PCB

ø5.5 DRILL THRU
/ø7.5 C'SINK

은무데드론 라벨

은무데드론 라벨

4.3/10 MINI DIN FEMALE

METRAL CONNECTOR(4X6) HEADER
RIGHT ANGLE SOLDER

2-PDM FEMALE

* ELECTRICAL SPECIFICATIONS

Service Band : PS800

Frequency range : DL - 851 ~ 869MHz

UL - 806 ~ 824MHz

Input V.S.W.R (Max.) : 1.4 : 1

PIM (Max.) : -156dBc (@43.0dBm 2Tone, CDMA)

Attenuation Value : -23.0 ± 1.0dB(DL, UL)

Flatness (Max.) : 2.0dB(DL)

Input Power (Max.) : 40W

Impedance : 50Ω


* MECHANICAL SPECIFICATIONS

HOUSING : A6061 T6 (White Chromate)

CONNECTOR(4.3/10) : MBsBD (SUCO Plate)

CONNECTOR PIN(4.3/10) : Beryllium Copper (Silver Plate)

INSULATORS : TEFLON



S/N : KYYWXXXX
Date : YYYY.MM

* 삽입손실 표기 내용

A : 860 MHz Insertion Loss

B : 815 MHz Insertion Loss

해당 주파수의 값을 수기로 표기 (ex : -23.3)

* Serial label 표기 내용

S/N : KYYWXXXX (YY : YEAR, WW: WEEK, XXXX : NUMBER)

Date : YYYY.MM (Date of manufacture)

TOLERANCE	Decimal	±0.3	DATE	2016. 03. 25.		RF & MICROWAVE TECHNOLOGY Tel : 82-32-347-8015 Fax : 82-32-347-8017
	Angle	±1°	APPROVED BY	J.H.YOUN		
MATERIAL	A6061 T6		CHECKED BY	S.L.SON	TITLE	PIMD ATTENUATOR
	FINISH		DRAWN BY	T.J.KIM		
White Chromate		SCALE	1/1	UNIT	mm	DWG NO. AT00108-7/2 REVISION 2 SHEET 1 of 1