

CF00024-7/1



SMA-PS+SMA-PS

+RG316DS

SMA PS RG316DS

BO/GO, PI/GO, CH/BR/NI

CF00024-7/1 350mm

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40°C ~ 125°C

**350mm - S11/S22/S21
(SWR, SWR, dB)**

■_1.0GHz	- 1.01, 1.01, 0.30
■_1.5GHz	- 1.07, 1.07, 0.39
■_2.0GHz	- 1.08, 1.09, 0.47
■_2.5GHz	- 1.06, 1.05, 0.54
■_3.0GHz	- 1.13, 1.13, 0.61

■_4.0GHz	- 1.21, 1.22, 0.72
■_5.0GHz	- 1.36, 1.38, 0.90
■_6.0GHz	- 1.25, 1.25, 0.93

► **NETWORK ANALYZER**

► **Test cable**

► **Test Adaptor**

■ E5071B (~8.5GHz)

■ N Male to SMA Male

■ SMA (J) SMA (J) ST

□ ZVA50 (~50GHz)

10GHz Cable (CF00540-7/1)

AD00006-7/2

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

