

CF00045-7/2



SMA-PS+SMA-PS
+85MF(BLUE)

SMA PS 85MF

BO/GO, PI/GO, CH/BR/NI

CF00045-7/2 1.5M 8G

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40°C ~ 125°C

1.5M
S11/S22/S21
(SWR, SWR, dB)

■_1.0GHz	- 1.01, 1.01, 1.00
■_2.0GHz	- 1.02, 1.03, 1.52
■_3.0GHz	- 1.06, 1.06, 1.88
■_4.0GHz	- 1.03, 1.05, 2.21
■_5.0GHz	- 1.12, 1.14, 2.49
■_6.0GHz	- 1.08, 1.12, 2.74
■_7.0GHz	- 1.09, 1.15, 3.00
■_8.0GHz	- 1.09, 1.16, 3.22
■_MaX/	1.17, 1.22, 3.34

► NETWORK ANALYZER

► Test cable

► Test Adaptor

■ E5071B (~8.5GHz)

■ N Male to SMA Male

■ SMA (J) SMA (J) ST

□ ZVA50 (~50GHz)

10GHz Cable (CF00540-7/1)

AD00006-7/2

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

