

CF00103-7/1



BNC-PS+BNC-PS

+RG174

BNC PS

BO/Ni PI/Go CC/BR/NI

CF00103-7/1 1.5M

Frequency	
Insertion Loss	
VSWR	
Impedance	☒ 50Ω ☐ 75Ω
Temperature	-40°C ~ 125°C

1.5M
S11/S22/S21
(SWR, SWR, dB)

■_0.5GHz - 1.18, 1.18, 1.00
■_1.0GHz - 1.26, 1.26, 1.51
■_1.5GHz - 1.21, 1.18, 1.85
■_2.0GHz - 1.33, 1.29, 2.27
■_3.0GHz - 1.52, 1.53, 3.05
■_4.0GHz - 1.25, 1.38, 3.56
■_5.0GHz - 1.45, 1.46, 4.18
■_6.0GHz - 1.25, 1.18, 4.55

► NETWORK ANALYZER

► Test cable

► Test Adaptor

■ E5071B (~8.5GHz)

■ N Male to SMA Male

■ BNC (J) SMA (J) ST

□ ZVA50 (~50GHz)

10GHz Cable (CF00540-7/1)

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

