

CF00142-7/2



BNC-PS+SMB-PS
+RG223(GRAY)

BNC PS

BO/NI, PI/GO, CAP/ZnDC/NI-KJ

SMB PS

BO/GO, PI/GO, CC/BR/GO

CF00142-7/2 1M

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40°C ~ 125°C

**1M - S11/S22/S21
(SWR, VSWR, dB)**

■_0.5GHz - 1.06, 1.05, 0.44
■_1.0GHz - 1.09, 1.09, 0.71
■_1.5GHz - 1.15, 1.13, 0.96
■_2.0GHz - 1.17, 1.13, 1.15
■_3.0GHz - 1.14, 1.15, 1.36

■_4.0GHz - 1.46, 1.54, 1.66

► NETWORK ANALYZER

► Test cable

► Test Adaptor

■ E5071B (~8.5GHz)

■ N Male to SMA Male

■ SMA (J) BNC (J) ST

□ ZVA50 (~50GHz)

10GHz Cable (CF00540-7/1)

■ SMA (J) SMB (J) ST

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

