

CF00166-7/2



SMA-PS+SMA-PS

+141F

SMA PS 141TP

BO/GO, PI/GO, CH/SUS

CF00166-7/2 203mm

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40°C ~ 125°C

203mm - S11/S22/S21
(SWR, SWR, dB)

■ _1.0GHz	- 1.02, 1.01, 0.15
■ _2.0GHz	- 1.02, 1.01, 0.23
■ _3.0GHz	- 1.05, 1.01, 0.29
■ _4.0GHz	- 1.03, 1.02, 0.33
■ _5.0GHz	- 1.01, 1.01, 0.40
■ _6.0GHz	- 1.04, 1.04, 0.44
■ _7.0GHz	- 1.17, 1.16, 0.50
■ _8.0GHz	- 1.22, 1.22, 0.57

► NETWORK ANALYZER

► Test cable

► Test Adaptor

■ E5071B (~8.5GHz)

■ N Male to SMA Male

■ SMA (J) SMA (J) ST

□ ZVA50 (~50GHz)

10GHz Cable (CF00540-7/1)

AD00006-7/2

TR1 : IN PORT VSWR(S11), TR2 : OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

