

CF00178-7/2



SMA-PL+SMA-PS

+85MF(BLUE)

SMA PL 85MF ONE/BODY

BO/GO, PI/GO, CH/BR/NI

SMA PS 85MF

BO/GO, PI/GO, CH/BR/NI

CF00178-7/2 0.5M

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40°C ~ 125°C

**0.5M - S11/S22/S21
(SWR, SWR, dB)**

■_1.0GHz	- 1.07, 1.07, 0.37
■_2.0GHz	- 1.10, 1.10, 0.52
■_3.0GHz	- 1.06, 1.06, 0.64
■_4.0GHz	- 1.06, 1.06, 0.75
■_5.0GHz	- 1.19, 1.20, 0.86

■_6.0GHz	- 1.23, 1.25, 0.98
■_7.0GHz	- 1.37, 1.40, 1.13
■_8.0GHz	- 1.49, 1.43, 1.27

► **NETWORK ANALYZER**

► **Test cable**

► **Test Adaptor**

■ E5071B (~8.5GHz)

■ N Male to SMA Male

■ SMA (J) SMA (J) ST

□ ZVA50 (~50GHz)

10GHz Cable (CF00540-7/1)

AD00006-7/2

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

