



CF00185-7/1 100mm	
Frequency	
Insertion Loss	
VSWR	
Impedance	☒ 50Ω ☐ 75Ω
Temperature	-40℃ ~ 125℃

100mm - S11/S22/S21 (SWR, SWR, dB)	
■_1.0GHz	- 1.03, 1.02, 0.10
■_2.0GHz	- 1.03, 1.02, 0.18
■_3.0GHz	- 1.01, 1.03, 0.23
■_4.0GHz	- 1.08, 1.10, 0.28
■_5.0GHz	- 1.15, 1.17, 0.33
■_6.0GHz	- 1.19, 1.21, 0.37

■_7.0GHz	- 1.19, 1.25, 0.46
■_8.0GHz	- 1.20, 1.24, 0.43

- ▶ NETWORK ANALYZER
- ▶ Test cable
- ▶ Test Adaptor
- ☒ E5071B (~8.5GHz)

☒ N Male to SMA Male

☐ ZVA50 (~50GHz)
- 10GHz Cable (CF00540-7/1)
- SMA (J) SMA (J) ST AD00006-7/2

■ N (J) SMA (J) AD00424-7/1

TR1 : IN PORT VSWR(S11), TR2 : OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

