

1 2 3 4 5 6

A

B

C

D

1 2 3 4 5 6

REVISION					
REV	DESCRIPTION	DRAWN	APPR	DATE	
IR	Initial Registration	H.J.LEE	I.C.KIM	2016. 08. 17.	

SMA SMA

2 4 1 3

D-CUTTING 5.9

HEX8.0

12.0 L

Notes

- 1. RoHS & Pb-FREE
- 2. CONNECTOR FINISHES
 - 2-1. SMA PS → BODY : Gold Plating
CONTACT : Gold Plating
CAP : Gold Plating
 - 2-2. SMA JB → BODY : Gold Plating
CONTACT : Gold Plating

Center conductor Dielectric Outer Shield Jacket

1.5 2.5 10.0

③번 CONNECTOR 탈피도

Center conductor Dielectric Outer Shield Jacket

3.5 4.5 12.5

②번 CONNECTOR 탈피도

4	BONDING TUBE	2	LS TUBE	ATU00008-N/1	Ø6-20 (Black)
3	CONNECTOR	1	KJ COMTECH	CN03286-7/6	SMA50 PL
2	CONNECTOR	1	KJ COMTECH	CN02005-7/2	SMA50 JB
1	COAXIAL CABLE		EXPANTEL	ACA00040-N/1	141FJ(50Ω) - BLUE

CUSTOMER	NO.	DESCRIPTION	Q'TY	VENDER	PART NO.	REMARKS
	DATE	2016. 08. 17.				
CUSTOMER CODE	APPROVED BY	I.C.KIM				
CABLE LENGTH TOLERANCE 0 ~ 1000mm : +5, -0 1000 ~ 2000mm : +10, -0 2000 ~ 3000mm : +15, -0 3000 ~ 4000mm : +20, -0 4000 ~ 5000mm : +25, -0 5000 ~ : +10%	CHECKED BY			KJ COMTECH RF & MICROWAVE TECHNOLOGY TEL : 02-02-043-8016 FAX : 02-02-043-8017		
	DRAWN BY	H.J.LEE				
	CHECKED BY					
	SCALE	UNIT				
	N/S	mm			TITLE CABLE ASS'Y	
			DWG NO.		CA08127-7/1	
			DETAIL NO.			
			REVISION		IR	SHEET 1 of 1

A4