

CF00350-7/1



TNC-PS+TNC-PS
+LMR400(CABLE/KOREA)
TNC PS
BO/NI, PI/GO, CH/BR/NI

CF00350-7/1 40M

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40°C ~ 125°C

40M - S11/S22/S21
(SWR, SWR, dB)

■_1.0GHz	- 1.12, 1.11, 5.90
■_2.0GHz	- 1.14, 1.12, 8.64
■_3.0GHz	- 1.08, 1.14, 10.90
■_4.0GHz	- 1.15, 1.17, 12.86

■_5.0GHz	- 1.31, 1.28, 14.82
■_6.0GHz	- 1.31, 1.31, 16.26
■_7.0GHz	- 1.19, 1.13, 17.66
■_8.0GHz	- 1.23, 1.15, 19.08

► NETWORK ANALYZER

► Test cable

► Test Adaptor

■ E5071B (~8.5GHz)

■ N Male to N Male

■ N (J) N (J) AD00379-7/2

□ ZVA50 (~50GHz)

10GHz Cable (CF00539-7/1)

TR1 : IN PORT VSWR(S11), TR2 : OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

