

CF00398-7/1

**CF00398-7/1 500mm**

Frequency	
Insertion Loss	
VSWR	
Impedance	■ 50Ω □ 75Ω
Temperature	-40°C ~ 125°C

500mm
S11/S22/S21
(SWR, SWR, dB)

■_1.0GHz	- 1.00, 1.02, 0.19
■_2.0GHz	- 1.05, 1.06, 0.29
■_3.0GHz	- 1.10, 1.10, 0.40
■_4.0GHz	- 1.04, 1.04, 0.44

■_5.0GHz	- 1.15, 1.15, 0.50
■_6.0GHz	- 1.36, 1.35, 0.63
■_7.0GHz	- 1.33, 1.33, 0.72
■_8.0GHz	- 1.50, 1.51, 0.88

SMA-PS+SMA-
PS+LMR240(CABLE/KOREA)
SMA PS LMR240
BO/NI, PI/GO, CH/BR/NI

▶ **NETWORK ANALYZER**▶ **Test cable**▶ **Test Adaptor**

■ E5071B (~8.5GHz)

■ N Male to SMA Male

■ SMA (J) SMA (J) ST

□ ZVA50 (~50GHz)

10GHz Cable (CF00540-7/1)

AD00006-7/2

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

