



SMA-PS+SMA-PS
+LMR200(TIMES)
SMA PS LMR200
BO/GO, PI/GO, CH/BR/NI

CF00400-7/2 3M

Frequency	
Insertion Loss	
VSWR	
Impedance	☒ 50Ω ☐ 75Ω
Temperature	-40°C ~ 125°C

3M - S11/S22/S21 (SWR, SWR, dB)

■_1.0GHz	- 1.16, 1.15, 1.13
■_1.5GHz	- 1.13, 1.13, 1.39
■_2.0GHz	- 1.09, 1.07, 1.60
■_2.5GHz	- 1.22, 1.20, 1.86
■_3.0GHz	- 1.04, 1.05, 2.01

■_4.0GHz	- 1.12, 1.09, 2.35
■_5.0GHz	- 1.29, 1.21, 2.72
■_6.0GHz	- 1.25, 1.19, 3.05

► NETWORK ANALYZER

► Test cable

► Test Adaptor

■ E5071B (~8.5GHz)

■ N Male to SMA Male

■ SMA (J) SMA (J) ST

□ ZVA50 (~50GHz)

10GHz Cable (CF00540-7/1)

AD00006-7/2

TR1: IN PORT VSWR(S11), TR2: OUT PORT VSWR(S22), TR3: Insertion Loss (S21)

